



Model	XMS-9060plus-G5i/i3200u/XP600/G5/G6					
	Honson/WUHAN/DPCS/UMC mainboard					
Appearance	Black grey + medium grey					
Print Head	Ricoh GEN5i/i3200u/G5/G6/XP600(1-8)					
Rail	Double rail					
Color	CMYK+Lc+Lm+White+Varnish					
Printing Speed (sqm/h)	dpi Printhead	GEN5	GEN6	GEN5i	i3200u	XP600
	720x600dpi (4PASS)	26m <sup>2</sup> /h	32m <sup>2</sup> /h	4m <sup>2</sup> /h	10m <sup>2</sup> /h	4m <sup>2</sup> /h
	720x900dpi(6PASS)	20m <sup>2</sup> /h	24m <sup>2</sup> /h	3m <sup>2</sup> /h	8m <sup>2</sup> /h	3m <sup>2</sup> /h
	720x1200dpi(8PASS)	15m <sup>2</sup> /h	18m <sup>2</sup> /h	2m <sup>2</sup> /h	6m <sup>2</sup> /h	2m <sup>2</sup> /h
Print size(mm)	940×640					
Print Thickness(mm)	Plate printing thickness0.1mm~175mm Cylinder print diameter 10mm~100mm (Ultra-high customizable)					
Curing System	LED UVLights					
Image Format	TIFF/JPG/EPS/PDF/BMP					
Rip Software	PHOTOPRINT/Maintop/Riin Rip-honson					
Negative pressure	White and color separate negative pressure					
Power Supply	AC220V 50HZ ± 10%					
Temperature	20-32°C					
Humidity	40-75%					
Power	2500W					
Appearance Size(mm)	Length /width /height:2490/2510/1430 (Trolley head adjustable height 175mm)					
Data Transmission	TCP/IP network interface					
Net Weight(kg)	600					
Wooden box size(mm)	Length /width /height:2600/2650/1550					
Suction system	750W brand fans					
Y-axis	Servo motordrive					
Lead screw	Imported brand double Y screw					
Automatic height measurement	The system drives the automatic height measurementfunction					